digital™ MATERIAL SAFETY DATA SHEET

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: March 4, 1992

Supersedes: September 3, 1990

Product Name: Screen Cleaner
Use: To Clean Computer Monitor Screens
(see product instructions for further details)

Part Number(s): VT3XX-SC

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST IARC	CARCINOGEN LIST NTP	CARCINOGEN LIST OSHA	SARA 313
Isopropyl Alcohol	67-63-0	18	400 ppm	400 ppm	NO	NO	NO	NO
Ammonia	7664-41-7	1.35	25 ppm	50 ppm	NO	NO	NO	YES
OTHER INGREDIENTS								
Water		79	Not applicable					
Dimethyl Benzylammonium-Chloride	68424-85-1	0.8	Not applicable					
Diazolidinyl-Urea	78491-02-8	0.2	Not applicable					
Methylparaben	99-76-3	0.12	Not applicable					
Propylparaben	94-13-3	0.03	Not applicable					
Fragrance confidential		0.5	Not applicable					

All chemicals contained in this product are on the US TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - 102°C (215°F)
Vapor Pressure - Not available
Vapor Density - 1.0 (air=1)
Appearance - Cloudy solution
Freezing Point - Not available
Melting/Softening Point - Not applicable
Solubility in Water - 100%
Percent Volatile - 99.995
Evaporation Rate - 0.8 (water=1)
Odor and Odor Threshold - Ammonia odor
pH - 8.1
Specific Gravity- 0.95 (water = 1)

© Digital Equipment Corporation. 1992. All rights reserved.

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None
Auto-Ignition Temperature - 456°C (852°F)
Unusual Fire or Explosion Hazards - None
Extinguishing Media - Not available
Special Fire Fighting Procedure - None
Flammable Limits - Not available
Hazardous Combustion Products -
Carbon monoxide,carbon dioxide

SECTION 5 - REACTIVITY DATA

Stability - Stable
Conditions to Avoid - Heat, sparks, flame
Hazardous Decomposition Products - Not available
Hazardous Polymerization -None
Incompatibility - Anhydrides, isocyanate monomer, organometallic combinations, strong oxidants, ethylene oxide and oleum

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- Exposure by inhalation and skin possible. Overexposure to liquid can cause burn to the eyes.
Animal Experiment-
Acute- Oral LD50- >5840 mg/kg (practically non-toxic); Dermal LD50- >16 g/kg; (slightly toxic); Inhalation - Saturated vapor not lethal to rats - 4 hours; Liquid may cause corrosion to eye.
Chronic/Other- Data show that there is no mutagenic hazard. There is no reproductive or carcinogenic hazard based on component data.
Additional Information- The ACGIH TLV for hazardous ingredients was established to protect against eye, nose and throat irritation.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

If Inhaled - Remove to fresh air. Support breathing if necessary and contact a physician.
If on Skin - Promptly wash skin with soap and water. If irritation persists after washing, contact a physician.
If in Eyes - Flush eyes with large quantities of water for at least 15 minutes. If irritation persists after washing, contact a physician.
If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Engineer Control - Not needed.
Waste Disposal - No special requirements.
Handling Procedure/Equipment- None
Procedures for Leaks or Spills- Wipe up with absorbent material.
WHMIS Classification- Class E-Corrosive
Personal Protective Equipment - None for normal use.
Work Practices - None
Labelling- US-Corrosive;
Storage Requirement- Do not store near heat, flames, sparks, strong oxidants or in aluminum cans.

SECTION 9 - TRANSPORTATION REQUIREMENTS

None

MSDS SATISFIES OSHA AND WHMIS REQUIREMENTS